





MARKET-PROVEN PLATFORM, DESIGNED AS AN ELECTRIC VEHICLE FROM THE GROUND UP

> (888) 589-6878 ZMTRUCKS.US

MODEL NAME



WEIGHTS CLASS 3 CLASS 4 GVWR 14,000 lbs 15,995 lbs PAYLOAD 9,380 lbs 7,385 lbs REAR AXLE 13.670 lbs 13.670 lbs FRONT AXLE 7,050 lbs 7,050 lbs CHASSIS CURB WEIGHT (CW) 6,615 lbs 6,615 lbs CHASSIS CURB WEIGHT REAR (CWR) 2,980 lbs 2,980 lbs

DIMENSIONS

CHASSIS/CAB LENGTH	234 in
WHEELBASE (WB)	138 in
HEIGHT (CAB)	116 in
WIDTH (CAB)	79 in
HEIGHT (TOP OF FRAME)	32 in
WIDTH (CHASSIS)	91 in
GROUND CLEARANCE (LOWEST POINT)	8 in
TURNING CIRCLE	41 ft

PERFORMANCE

RANGE (WLTP)	220 miles	190 miles
TOP SPEED	65 mph	
POWER (CONTINUOUS/PEAK)	150 / 270 hp	
TORQUE (CONTINUOUS/PEAK)	170 / 330 lb/ft	
TRACTION MOTOR LOCATION	REAR E-AXLE	
ePTO #1	15 kW	
ePTO #2	30 kW	

CHASSIS

APPROACH ANGLE (FRONT)	19 degrees
DEPARTURE ANGLE (REAR)	17 degrees
BRAKE SYSTEM	HYDRAULIC
BRAKE TYPE (F/R)	DISC/DISC
SAFETY FEATURES	ABS/ABD/ESC/TPMS/PWS
ADAS FEATURES	AEB/LDW
FRONT SUSPENSION	LEAF
REAR SUSPENSION	LEAF
TIRE SIZE	225/70 R19.5

HIGH VOLTAGE

HV BATTERY CAPACITY	132 kWh
HV BATTERY VOLTAGE	600 V
AC LEVEL 2 CHARGE 20%-100%	6 hrs @ 20 kW
DC FAST CHARGE 20%-80%	40 min @ 135 kW
HV BATTERY LOCATION	INSIDE FRAME
CHARGE CONNECTION	CCS1

CAB

LOW VOLTAGE NOMINAL	24 V
HEATING CAPACITY	3,000 W
COOLING CAPACITY	4,500 W
AC REFRIGERANT	1234YF
CRUISE CONTROL	STD
SEATING	2
DRIVERS SEAT ADJUSTMENT	4 WAY ADJUSTABLE AND HEATED
REAR VIEW CAMERA	STD
REARVIEW MIRRORS HEATED	STD
REARVIEW MIRRORS ELEC. ADJUST	STD
HEADLIGHTS	LED
EXTERIOR LIGHTS	LED
INFOTAINMENT	AM, FM, BLUETOOTH, USB-A
DASHBOARD SCREEN SIZE	7 in
INFOTAINMENT SCREEN SIZE	12.3 in

UPFITTER

FRONT AXLE TO BACK OF CAB (AC)	21 in
FRONT BUMPER TO FRONT AXLE (BA)	44 in
FRONT BUMPER TO BACK OF CAB (BBC)	65 in
CARGO BODY LENGTH (FROM/TO) (BL)	14 ft
CAB TO AXLE (CA)	111 in
CAB TO BODY CLEARANCE (CB)	4 in

For more information, please contact us at:

INFO@ZO-MOTORS.COM

Please visit our website:

ZMTRUCKS.US